

LED SPOT LIGHT
SP-R40/R100/R120



SP-R40



SP-R100B



SP-R120

- Bright color
- Good monochrome
- Soft light, low power
- long life, luminous time up to 50,000 hours



Half shield




Round shield




Sharp spike




Physical&Installation Dimensions




SP-R40A



SP-R100B



SP-R120



SPIKE

Model Info&Specifications

Model	Diameter	Power(Max)	Colours	Lumen	Beam Angle	Control	Chips Brand	Package
SP-R40A -1P	φ42	2.3W	2700K/3000K 4000K/6000K	223 lm	10° /15° /20° 25° /30° /40° 55° /60°	DMX ON OFF Tunable White DALI2 0-10V	EPISTAR OSRAM CREE San'an BRIDGELUX	0.35±5%Kg 20 Units/Ctn 40*40* 38.5CM
SP-R40A -3P	φ42	3W	R+G+B	110 lm				0.35±5%Kg 20 Units/Ctn 40*40* 38.5CM
SP-R100B -3P	φ99	7W	2700K/3000K 4000K/6000K	630 lm				1.0±5%Kg 18 Units/Ctn 40*40*38.5CM
SP-R100B -3P	φ99	9W	RGBW	405 lm				1.0±5%Kg 18 Units/Ctn 38*38*31CM
SP-R120A -6P	φ120	14W	2700K/3000K 4000K/6000K	1260 lm				1.2±5%Kg 18Units/Ctn 40*40* 38.5CM
SP-R120A -18P	φ120	18W	R+G+B	560 lm				1.2±5%Kg 18 Units/Ctn 40*40*38.5 CM

